PS22S-4NCBR-N2P

Intelligent Push Button
4-Wire DC Static
Annular bezel: *Standard*

Mind O≠0, I≠l≠1, S≠5, B≠8.

Activation	push
Thread	M22×1
Operating mode	static
Operating voltage V_+	10...35 V_{DC}
Reverse polarity protection	built-in
Current consumption	<50 mA @ 35 V_{DC}
Current load capability	200 mA
Short circuit protection	built-in – self resetting
Input threshold high|low	0.45 × V_+ | 0.55 × V_+
Impedance	15 kΩ
Output polarity	NPN
Output function	⎍ normally closed
Number of operations	10^8...10^9
Indicator LED idle↔pushed	blue↔red
Operating temperature	−40...+60 °C
IP Code (front)	IP 69k
IP Code (rear)	IP 67
IK impact protection (front)	IK 09
Sensing face material	polycarbonate
Annular bezel material	stainless steel 1.4305
Connection	2 m cable
Complies with	CE, RoHS

idle

pushed

The photos show the same model with M8 male connector and with a pictogram as a sample.

Warranty Our products are manufactured to stringent ISO 9001 European standards to ensure that our customers only receive the best quality.

Wiring diagram





Caution! This device shall not be used if the safety of persons rely on its faultless function.

XECRO reserves the right to make minor changes without prior notification.