TF22C-3NCWR-3U12

Mind O≠0, I≠l≠1, S≠5, B≠8.

Intelligent Touch Button
3-Wire DC Combo
Annular bezel: *Flush*

Activation	touch
Thread	M22×1
Operating mode	combination
Operating voltage	14...35 V_{DC}
Reverse polarity protection	built-in
Current consumption	<50 mA @ 35 V_{DC}
Current load capability	200 mA
Short circuit protection	built-in – self resetting
Output polarity	NPN
Output function	⅄ normally closed
Number of operations	10^8...10^9
Indicator LED idle↔touched	white↔red
Operating temperature	−40...+60 °C
Protection class (front)	IP 69k
Protection class (rear)	IP 67
Mechanical protection class (front)	IK 09
Sensing face material	polycarbonate
Annular bezel material	stainless steel 1.4305
Connection	30 cm cable, M12
Complies with	CE, RoHS

idle

touched

The photos show the same model with M8 male connector and with a pictogram as a sample.

25 months **Warranty** Our products are manufactured to stringent ISO 9001 European standards to ensure that our customers only receive the best quality.

Wiring diagram



Pinout





Caution! This device shall not be used if the safety of persons rely on its faultless function.

XECRO reserves the right to make minor changes without prior notification.